


HAZARD RATING
 4-EXTREME
 3-HIGH
 2-MODERATE
 1-SLIGHT
 0-INSIGNIFICANT



MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Date Prepared: 2-15-12

SECTION 1 - PRODUCT IDENTIFICATION

Company Name	Steam Way International, Inc.	Emergency Telephone No.	800-535-5053
Address	P.O. Box 514, Jackson, WY 83001	Information Telephone No.	800-447-8326
Product Name / ID#	FabriCover II (60564)	Product Type	Fabric Protectant <input checked="" type="checkbox"/> Proprietary Product

SECTION 2 - HAZARDOUS INGREDIENTS

Chemical Name/Common Name	Cas No.	Percent (optional)	TLV (Source)
Naphtha, Petroleum	8052-41-3	< 100 %	100 ppm (ACGIH)
			500 ppm (OSHA-PEL)

* Substances Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.

SECTION 3 - PHYSICAL DATA

Boiling Point (°F)	>315°F	Specific Gravity (H ₂ O=1.0)	0.772 ± 0.005	pH	NA	% VOC (ww)	95 %
Solubility In Water	<input type="checkbox"/> Complete <input checked="" type="checkbox"/> Insoluble <input type="checkbox"/> Emulsifiable or (Dispersible) <input type="checkbox"/> Slight (or Partial)						
Evaporation Rate (vs H ₂ O)	<input checked="" type="checkbox"/> Faster <input type="checkbox"/> Slower <input type="checkbox"/> About the Same			Vapor Pressure	3.00	Vapor Density	4.70

Appearance and Odor Clear, colorless liquid. Solvent type odor.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (T.C.C.) 105°F None to boiling Flammable Limits Upper NE Lower NE

Extinguishing Media Dry chemical, foam or carbon dioxide.

Special Fire Fighting Procedures Use water spray to cool fire exposed containers. Wear self-contained breathing apparatus.

Unusual Fire Explosion Hazards None

SECTION 5 - REACTIVE DATA

Stability Stable Incompatibility Avoid strong oxidizing & reducing agents.

Hazardous Decomposition Products Combustion may yield Carbon Monoxide and/or Carbon Dioxide.

SECTION 6 - HEALTH HAZARDS

Threshold Limit Value Product See Section 2 for Ingredients TLV None Established Not Applicable Primary routes of Exposure Eyes Skin Oral Inhalation

Signs Symptoms of Over-exposure (Acute) May cause mild eye irritation. Causes skin irritation. Breathing high concentrations of vapors may cause irritation of the nose, throat and signs of nervous system depression (i.e. headache, dizziness, etc).

Ingestion of excessive quantities may cause irritation of the digestive tract.

Signs Symptoms of Over-exposure (Chronic) Unknown

Medical Conditions Aggravated by Over-exposure Pre-existing skin & lung disorders.

Carcinogen/Suspected Carcinogen Ingredients: NTP IARC OSHA None

SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)

Eyes Flush with water for 15 minutes.

Skin Wash affected area with plenty of soap & water for 5-10 minutes. Remove contaminated clothing and wash before reuse.

Ingestion Do NOT induce vomiting or give anything by mouth as possibility of product reaching the lung and causing damage.

Inhalation If qualified, give oxygen or artificial respiration as needed and/or seek medical help.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection If concentration exceeds exposure limit, use NIOSH approved respirator for organic vapors.

Ventilation requirements Local Exhaust Mechanical To keep below any listed TLV's and/or for general good ventilation.

Protective Gloves Rubber Eye Protection Safety glasses or goggles

Other Protective Clothing Other impervious clothing should be worn as needed to prevent skin contact.

SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken if Released or Spilled Dike area to contain spill. Absorb material into appropriate absorbent material.

Waste Disposal Methods Place in D.O.T. approved drum. Check all government regulations for disposal.

SECTION 10 - STORAGE AND HANDLING INFORMATION

Precautions to be Taken in handling and Storage Store in well ventilated, cool area in tightly closed containers. Keep out of reach children. Wash thoroughly after handling.