


HAZARD RATING
 4-EXTREME
 3-HIGH
 2-MODERATE
 1-SLIGHT
 0-INSIGNIFICANT



MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Date Prepared: 2-15-12

SECTION 1 - PRODUCT IDENTIFICATION

Company Name Steam Way International, Inc. Emergency Telephone No. 800-535-5053
 Address P.O. Box 514, Jackson, WY 83001 Information Telephone No. 800-447-8326
 Product Name / ID# Wall Cleaning Liquid (699) Product Type Alkaline / Solvent Cleaner Proprietary Product

SECTION 2 - HAZARDOUS INGREDIENTS

Chemical Name/Common Name	Cas No.	Percent (optional)	TLV (Source)
Dipropylene glycol methyl ether	34590-94-8	< 15%	100 ppm(skin)
Sodium Hydroxide	1310-73-2	< 5%	C 2 mg/m3 (ACGIH)

* Substances Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.

SECTION 3 - PHYSICAL DATA

Boiling Point (°F) Approx. 212°F Specific Gravity (H₂O=1.0) 1.084 ± 0.005 pH 13.0 ± 0.5 % VOC (ww) 10.8%
 Solubility In Water Complete Insoluble Emulsifiable or (Dispersible) Slight (or Partial)
 Evaporation Rate (vs H₂O) Faster Slower About the Same Vapor Pressure NE Vapor Density NE

Appearance and Odor Clear, amber non-viscous liquid. Glycol ether odor.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (T.C.C.) >200°F None to boiling Flammable Limits Upper NA Lower NA

Extinguishing Media CO 2, Dry Chemical, water fog

Special Fire Fighting Procedures None

Unusual Fire Explosion Hazards None

SECTION 5 - REACTIVE DATA

Stability Stable Incompatibility Strong Acids, Oxidizers

Hazardous Decomposition Products Oxides of carbon.

SECTION 6 - HEALTH HAZARDS

Threshold Limit Value Product See Section 2 for Ingredients TLV None Established Not Applicable Primary routes of Exposure Eyes Skin Oral Inhalation

Signs Symptoms of Over-exposure (Acute) May cause burns to eyes and skin. Excessive inhalation may cause headaches or dizziness. If ingested may cause burns to mouth and throat and also nausea, vomiting, abdominal pain. Possibility of harmful absorption through skin.

Signs Symptoms of Over-exposure (Chronic) Unknown

Medical Conditions Aggravated by Over-exposure May aggravate existing dermatitis.

Carcinogen/Suspected Carcinogen Ingredients: NTP IARC OSHA None

SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)

Eyes Flush with water for 15 minutes. If relief is not readily apparent, seek medical help.

Skin Wash with plenty of water. Remove any contaminated clothing and wash before reuse.

Ingestion Give large amounts of water. Do NOT induce vomiting. Get medical attention immediately.

Inhalation Remove to fresh air. If qualified, give oxygen or artificial respiration as necessary and/or seek medical help.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection None. If general good ventilation maintained. Use organic vapors respirator in high vapor conditions.

Ventilation requirements Local Exhaust Mechanical To keep below any listed TLV's and/or for general good ventilation.

Protective Gloves Rubber Gloves Eye Protection Chemical Goggles

Other Protective Clothing Rubber apron recommended when handling larger volumes

SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken if Released or Spilled Contain spill. Neutralize with mild acid. Vacuum up or absorb on inert material. Rinse any residue with large amount water.

Waste Disposal Methods Check all government regulations. May be possible to flush neutralized material to sanitary sewer with plenty of water.

SECTION 10 - STORAGE AND HANDLING INFORMATION

Precautions to be Taken in handling and Storage Keep out of reach of children. Wash thoroughly after handling.